

DRY CARGO

SIZE	Exterior Dimensions (mm)			Interior Dimensions (mm)			Door Openings (mm)		Weight (kg)			Volume (m3)
	Length	Width	Height	Length	Width	Height	Width	Height	Gross	Tare	Payload	
20'GP	6,058	2,438	2,591	5,898	2,352	2,393	2,340	2,280	30,480	2,100	28,380	33.2
40'GP	12,192	2,438	2,591	12,032	2,352	2,393	2,340	2,280	32,500	3,500	29,000	67.7
40'HC	12,192	2,438	2,896	12,032	2,352	2,698	2,340	2,585	32,500	3,700	28,800	76.4

REEFER

SIZE	Exterior Dimensions (mm)			Interior Dimensions (mm)			Door Openings (mm)		Weight (kg)			Volume (m3)
	Length	Width	Height	Length	Width	Height	Width	Height	Gross	Tare	Payload	
20'GP	6,058	2,438	2,591	5,456	2,294	2,273	2,290	2,264	30,480	2,840	27,640	28.4
40'HC	12,192	2,438	2,896	11,588	2,294	2,554	2,290	2,569	34,000	4,510	29,490	67.9

OPEN TOP

SIZE	Exterior Dimensions (mm)			Interior Dimensions (mm)			Door Openings (mm)		Weight (kg)			Volume (m3)
	Length	Width	Height	Length	Width	Height	Width	Height	Gross	Tare	Payload	
20'	6,058	2,438	2,591	5,895	2,352	2,348	2,340	2,280	30,480	2,300	28,180	32.5
40'	12,192	2,438	2,591	12,029	2,352	2,348	2,340	2,280	30,480	3,920	26,560	65.9

FLATRACK

SIZE	Exterior Dimensions (mm)			Interior Dimensions (mm)			Weight (kg)		
	Length	Width	Height	Length ※1	Width ※1	Height ※2	Gross	Tare	Payload
20'	6,068	2,438	2,591	5,612	2,227	2,213	34,000	2,740	31,260
40'	12,202	2,438	2,591	11,776	2,230	1,955	45,000	4,900	40,100

※1 Between cornerposts
 ※2 Side rail to top casting